

# WEBER


PRÜFTECHNIK

**LWD WEBER**  
*connect*



## Cables are a thing of the past!

- Wireless connection - no measuring cable
- Printer inside the handheld
- Menu control via colour touchscreen
- Virtual keypad to label the measurements in an easy way
- More than 200 measurements with one charge of the battery
- One mains adapter charges both batteries at the same time
- Maximum charging time: 3 hours
- High-quality coating against corrosion and long-lasting protection against environmental influences



# WEBER

PRÜFTECHNIK

## Technical data sheet - LWD WEBERconnect

### Handheld:

Dimensions:

Length: 203mm

Width: 108mm

Height: 40-55mm



### Equipment:

colour touchscreen without a pen, thermal printer with paper roll for 64 printouts, 4GB SD-card and card slot, GPS module, high-performance battery, backup battery, radio path to load plate with a transmission range up to max. 10m, battery charge indicator, internal storage for thousands of measurements, automatic menu navigation with beep-tone confirmation, three-colour display of the measurement curves, three language series - many languages available, virtual keypad to label the records, energy-saving option, mains adapter with all common worldwide adapters

### Loading device

**10 kg**

Dimensions:

Height: 115mm

Diameter: 235mm

Mass of the falling weight:

10kg

Total weight: 15kg

Drop height approx. 72cm



### Equipment:

weight with ball bearing, 17 plate springs, square handle with long support against rolling motion during transport, circular level, index bolt stainless steel as transport lock, galvanised coating

### Load plate

Dimensions:

Diameter: 300mm

Plate thickness: 20mm

Total height: 130mm

Weight: 15kg



### Equipment:

Electronic board with acceleration sensor, charging socket and battery, switch with monitoring light, transmitter for radio path up to max. 10m, slots for attaching transport cart, two handles, galvanic coating

**LWD WEBERconnect**  
**...und alles im**  
**Grünen**